

RDH Building Engineering Ltd.


**STUDY OF POURED-IN-PLACE CONCRETE WALLS:
UPDATE ON CURRENT TRENDS**

Sponsors

CMHC SCHL

Homeowner Protection Office


Brian Hubbs, P.Eng.
RDH Building Engineering Ltd.



RDH Building Engineering Ltd.

AGENDA


- Introduce the study
 - Most of you have already seen at least 1 presentation at BCBE, Willis etc..
 - A CD version of the study has been provided
- Review new case studies from recently constructed buildings and discuss based on study recommendations



RDH Building Engineering Ltd.

www.rdhbe.com

Poured-In-Place Concrete Wall Assemblies



RDH Building Engineering Ltd.

www.rdhbe.com

RDH Building Engineering Ltd.

Study Case Studies 1-4

- Eight buildings were reviewed to provide background information and bias for the study.
- Building age ranged between, 5, 13 and 23 years old and 4 towers under construction. Height ranging from 8 to 40 stories
- Some evidence of water infiltration was observed on all buildings. Older buildings had evidence of previous water infiltration and some mold was observed on the exterior of the interior gypsum board. Signs of water infiltration were related to the following conditions:
 - Cold and control joints
 - Tie holes
 - Honeycombed area of concrete
 - Window, louver and roof interface details
 - Cracks through the concrete
 - Concrete interface with adjacent rainscreen wall assemblies


RDH Building Engineering Ltd.

www.rdhbe.com

Rain Penetration Control Strategy

- For uncracked wall area rain penetration control relies on:
 - Water shedding at the surface of the concrete
 - Concrete absorbing moisture and subsequent drying to the exterior
- Redundancy is achieved
- What happens at cold joints and cracks?

99%




RDH Building Engineering Ltd.

www.rdhbe.com

RDH Building Engineering Ltd.

Building Form and Pour Configurations

- Alternate arrangements of overhangs and poured-in-place concrete wall configurations create differing levels of risk




LOWEST RISK

Good overhang protection provided by slab projection. Concrete wall is in compression due to vertical loads and no vertical cold joints used

RDH Building Engineering Ltd.

www.rdhbe.com

Building Form and Pour Configurations




MORE RISK

Good overhang protection provided by slab projection. Use of upstand wall under window creates vertical cold and uncompressed infill concrete element (no significant vertical loads)

RDH Building Engineering Ltd. www.rdhbe.com

Building Form and Pour Configurations




MORE RISK

No overhang protection. Only exposed concrete occurs between windows and is in compression. No vertical control joints used

RDH Building Engineering Ltd. www.rdhbe.com

Building Form and Pour Configurations



MOST RISK (Monolithic pour is even higher risk)

No overhang protection. Use of upstand wall under window creates vertical cold and uncompressed concrete element

RDH Building Engineering Ltd. www.rdhbe.com

Key Points – Poured-In-Place Concrete Walls

- The risky part of a concrete wall assembly from a rain penetration perspective are locations of cracks and joints
- Manage rain penetration at joints and cracks
 - Minimize number and size of cracks
 - Encourage them to occur at predictable locations – control joints
 - Provide two lines of defense at all interfaces and joints (redundancy)
 - Building form and pour configurations that limit exposure conditions
- Due to the lesser certainty in predicting the location of cracks and the variable damming characteristics of waterstop materials there will always be greater risk of water penetration associated with poured-in-place concrete walls than with most rainscreen wall assemblies
- Water penetration issues are likely to be localized problems
- Thermal issues are important too (Energy and Condensation)

RDH Building Engineering Ltd. www.rdhbe.com

Three New Case Studies

- Constructed within the last four years
- High-rise construction
- Reported water infiltration, condensation and/or mold
- Cast in place concrete with exterior acrylic coating
- Within 5 year new home warranty period

RDH Building Engineering Ltd. www.rdhbe.com

Case Study 1


- No reported water infiltration
- 20% of respondents reported condensation issues
- 20% of respondents reported mold/mildew issues

RDH Building Engineering Ltd. www.rdhbe.com

Case Study 1 – As Built

I Typical exterior wall

1. Concrete wall
2. Concrete slab
3. Steel stud framing
4. Fibreglass batt
5. Gypsum wall board & VB
6. Control joint
7. Steel reinforcing





RDH Building Engineering Ltd. www.rdhbe.com

Case Study 1 – As Built

I Concrete detailing



1. Concrete wall
2. Concrete slab
3. Reveal (control joint – no caulking)
4. Typical crack locations
5. Reduced thickness
6. Construction joint (no caulking)

RDH Building Engineering Ltd. www.rdhbe.com

Case Study 1 - Walls

I Deficiencies - Cracking






U Window sill
S Window corner

RDH Building Engineering Ltd. www.rdhbe.com

Case Study 1 - Walls

I Deficiencies - Cracking






U Slab joint
S Saddle interface

RDH Building Engineering Ltd. www.rdhbe.com

Case Study 1 - Walls

I Deficiencies - Cracking






S Parapet walls
V

RDH Building Engineering Ltd. www.rdhbe.com

Case Study 1 - Walls

I Deficiencies - Cracking

S Miscellaneous
Crushed Duct
Inadequate Louver

RDH Building Engineering Ltd. www.rdhbe.com

Good Practice - Coatings

Table 3.6: Comparison of Coatings

Property	Acrylic Latex Paint	Acrylic Latex Emulsion	Epoxy Resin
Resistance (psi)	2.5	10.0	50
Crack Bridging	Poor	Good	Excellent
Flexibility	Good	Good	Excellent
Resistance to Abrasion (sand/cement)	1	2.2	5
Water Penetration Resistance	Good	Good	Excellent
Adhesion (psi)	Good	Good	Excellent
Resistance to Salt	2	2	2.2
Life Expectancy (Years)	3-5	5	50
Application (Environment)	Good	Good	Poor to Good
Surface Preparation	Easy	Easy	Difficult
Cost (per sq. ft.)	Low	Low	Excellent
Ease of Cleanup	Excellent	Excellent	Very Difficult




Figure 3.5c: Concrete moisture content for wall W3 with NC, BE and AE exterior coatings. Water content shown in units of kilograms per cubic meter.

www.rdhbe.com

Case Study 1 - Walls

Exploratory openings




Cracks in concrete and evidence of past water ingress
Very little damage to wall assembly at this time

RDH Building Engineering Ltd.

www.rdhbe.com

Case Study 1 – Crack Testing - Walls

- 2 cracks were tested for water infiltration by wetting the crack from the exterior without depressurization of the unit.
- One of the tested cracks allowed water infiltration to the interior after 30 seconds.



RDH Building Engineering Ltd.

www.rdhbe.com

Case Study 1 – Good Practice

- Concrete wall
- Concrete slab
- Control joint at u/s slab (Waterstop + exterior caulking)
- Control joint t/o slab (Waterstop + exterior caulking)
- Control joints below window corners (Waterstop + exterior caulking)




RDH Building Engineering Ltd.

www.rdhbe.com

Case Study 1 - Windows & Doors


Sill detail



RDH Building Engineering Ltd.

www.rdhbe.com


Windows & Doors – Good Practice



RDH Building Engineering Ltd.


www.rdhbe.com

Case Study 1 – Balconies and Decks



RDH Building Engineering Ltd.

Good Practice - Balcony Details



RDH Building Engineering Ltd.

Case Study 1 – Waterproofing



RDH Building Engineering Ltd.

Water Feature




RDH Building Engineering Ltd.

Case Study 2

- Numerous reports of water infiltration, condensation and mold/mildew issues

RDH Building Engineering Ltd.

Case Study 2 – Typical Deterioration and Fungal growth



RDH Building Engineering Ltd.


Case Study 2 – Inadequate Location for Architectural reveals



RDH Building Engineering Ltd.

www.rdhbe.com

Case Study 2 – No crack control planning = Cracks everywhere



RDH Building Engineering Ltd.

www.rdhbe.com


Case Study 2 – No crack control planning = Cracks everywhere



RDH Building Engineering Ltd.

www.rdhbe.com


Case Study 2 – No crack control planning = Cracks everywhere



RDH Building Engineering Ltd.

www.rdhbe.com

Joints - Good Practice



RDH Building Engineering Ltd.

www.rdhbe.com

Case Study 2 – Decks and Eyebrows



RDH Building Engineering Ltd.

www.rdhbe.com


Case Study 2 – Water Testing



RDH Building Engineering Ltd.

www.rdhbe.com

Case Study 2- Delamination of sealant and P&S membrane at jambs



RDH Building Engineering Ltd.

www.rdhbe.com

Case Study 3

Several reports of water infiltration and condensation

RDH Building Engineering Ltd.

www.rdhbe.com

Case Study 3 – Lack of Control Joints



RDH Building Engineering Ltd.

www.rdhbe.com

Case Study 3 – Cracked concrete leak



RDH Building Engineering Ltd.

www.rdhbe.com

Case Study 3 – Planter interface leak



RDH Building Engineering Ltd.

www.rdhbe.com


Case Study 3 – Dye test to isolate leakage path at curb wall interface



RDH Building Engineering Ltd.

www.rdhbe.com


Case Study 3 – Dye test at curb wall interface



RDH Building Engineering Ltd.

www.rdhbe.com


Case Study 3 – Water leakage through crack at wall/slab cold joint



RDH Building Engineering Ltd.

www.rdhbe.com

Waterproofing – Case Studies as-built




- Poorest Performance
 - Membrane can be maintained and replaced
 - Cracks in concrete curb allow water to interior side of waterproof membrane
 - Water flows laterally to ends or cracks and enters interior
 - Locating leakage paths very difficult

- Better performance
 - Water entering at cracks flows to exterior
 - Rebar penetration always under water, potential leakage path as bar corrodes
 - Membrane can not be repaired, maintained or replaced without curb removal or significant alteration of aesthetics
 - Membrane pre-stripping is often damaged at the edge during construction requiring curb removal to make proper transition, this is rarely done creating a weak point at critical location

www.rdhbe.com

Waterproofing – Good Practice



- Best Performance
 - Removable precast protects and allows membrane maintenance and replacement
 - Membrane can be installed in one application allowing proper quality control

- Good Compromise
 - Water entering at cracks flows to exterior
 - Rebar penetration always above water ponding level
 - Membrane can be repaired, maintained or replaced without curb removal
 - Membrane pre-stripping is coated over at transition when main field membrane is installed

RDH

www.rdhbe.com

Case Study 3 – Dye test of unsealed crack between up stand curb and wall



RDH Building Engineering Ltd.

www.rdhbe.com

Case Study 3 – Poor interface details



RDH Building Engineering Ltd.

www.rdhbe.com

Case Study 3 – Root damage



RDH Building Engineering Ltd.

www.rdhbe.com

Questions

RDH Building Engineering Ltd.

www.rdhbe.com